



AGILITY TECHNOLOGIES

RESCUE CAMERA COMPARISON

| Manufacturer: | Agility Technologies | Savox Communications | Yone Corporation | Groupe Leader / Leader Group |
|---|--|---|---|---|
| Website Links: | http://www.agilitycorp.com/firstlook360/ | https://www.savox.com/products/searchcam-3000/?compare=add_ | http://yone-co.co.jp/english/products/proeye-951-s-model2011/ | http://www.leader-group.eu/search-rescue/life-detectors-locators/search-cameras/search-camera-with-communication-leader-cam-1522-c230.html |
| Camera Model | Firstlook 360 | SC3000 | ProEye 951-S | Leader Cam |
| Camera Head Diameter < 2" | ✓ | ✓ | ✓ | ✓ |
| 360 Spherical Imaging | ✓ | ✗ | ✗ | ✗ |
| Motorized Mechanical Camera Head Articulation | ✗ | ✓ | ✓ | ✓ |
| Wireless connection to Camera Head | ✓ | ✗ | ✗ | ✗ |
| Wired connection to Camera Head | ✓ | ✓ | ✓ | ✓ |
| Spherical Still Image Capture | ✓ | ✗ | ✗ | ✗ |
| Still Image format | Jpeg | Jpeg | No | No |
| Spherical HD video recordings w/ audio | ✓ | ✗ | ✗ | ✗ |
| Hot swappable batteries | ✓ | ✓ | ✗ | ✗ |
| Operational Time (single set of batteries- typical use) | 3-4 hours * | 2 hours | 1.5hrs | 4.5 Hours |
| Recharge Time | 1.5 hours | 3 hours | 15min*** | 4hours |
| LED Illumination | ✓ | ✓ | ✓ | ✓ |
| Illumination Intensity Adjustment | ✓ | ✓ | ✓ | ✓ |
| Free Remote Viewer App for shared video | ✓ | ✗ | ✗ | ✗ |
| Total field of vision | 360x300 FoV | 240 degrees by repositioning Camera head | 180 degrees by repositioning Camera head | 170 degrees by repositioning Camera head |
| Resolution | 1080s HD Spherical Video | 811(H) X 507(V) | 795x595 | N/A |
| Multiple viewing screen capable | ✓ | ✓ | Requires Optional Proprietary Remote Monitor | ✗ |
| In the Field, Software Upgrades & Additional Features | ✓ | ✗ | ✗ | ✗ |
| Expandable Memory | SD Card (256G Max) + internal | SD Card 32G max | Only available with Optional A/V Recorder | ✗ |
| Virtual Joystick | ✓ | ✗ | ✗ | ✗ |
| VR Headset Compatible | ✓ | ✗ | ✗ | ✗ |
| Touch Screen Mute /Volume/PTT Controls | ✓ | ✗ | ✗ | ✗ |
| Selectable Left or Right handed control orientation | ✓ | ✗ | ✗ | ✗ |
| Sharing via secure cloud services | ✓ | ✗ | ✗ | ✗ |
| Two way voice communication | ✓ | ✓ | With Optional Audio System | ✓ |
| Date & Time Stamp stored on all recorded Images and video | ✓ | ✓ | ✗ | ✗ |
| Map overlay wth GPS Coordinates | ✓ | ✗ | ✗ | ✗ |
| Alternative Battery Power | CR123 Li | ✗ | ✗ | AAAcCell |
| Replaceable Lens | ✓ | ✗ | ✗ | ✗ |
| Multi Language Support ** | ✓ | N/A | N/A | N/A |
| Screen Resolution | 2048x1536 (QXGA) Samed Tablet | 960 X234 | 795X595 | N/A |
| Screen Size | 9.7" | 5" LCD | 5.6" LCD | 7" TFT LCD |
| Camera Head IP Rating | IP68 (2 meters) | IP68 (23 meters) | Raindrop | IP68 (2 Meters with Plug) |
| Telescoping Pole | 3m | 2.5m | 2.5m | 2.4m |
| NOTES: | | | | |
| N/A | Information not attainable at time of writing | | | |
| * | Up to 5 Hours depending on usage of Lighting , Live streaming and Audio | | | |
| ** | Software can be modified to accommodate different Languages. Contact Agility for additional costs | | | |
| *** | Recharge Specification taken from Yone 951-S Brochure claims 15 Minutes recharge to full capacity -please clarify this specification with Yone | | | |
| Disclosure | Product information has been gathered herein originates from information from Manufacturers websites, Product Brochures and Technical Specification documents available in the public domain. This comparison was compiled without malice to assist rescue professionals tasked with the selection of visual search equipment. Agility Technologies takes no responsibility for errors and/or omissions in other manufacturers' information. | | | |

AGILITY TECHNOLOGIES CORP.

#255 – 3757 Jacombs Road, Richmond, BC. V6V-2R3
p. 604.259.1579 e. info@agilitycorp.com w. agilitycorp.com